



Finnexx MOTO GUZHI SL/CF Oil

4-Stroke Motorcycle Oil

PRODUCT DESCRIPTION

Finnexx MOTO GUZHI SL/CF Oils 15W-40 and 20W-50 are high quality multigrade, multifunctional fluid specifically designed for use in four-stroke motorcycle engines, clutches and gear boxes, and portable power equipment engines requiring API SL/CF lubricants.

CUSTOMER BENEFITS

- **Cost-effective engine protection**
Proven formula protects contact surfaces to control engine and gear wear.
- **Dependable performance**
Special detergent and dispersant system combats build-up of piston and ring deposits to help maintain your engine's power and performance.

APPLICATIONS

- Air and liquid-cooled, four-stroke motorcycle engines
- Motorcycles with oil-immersed clutches (where oils of this performance level and viscosity grade are appropriate)
- Motorcycles with centrifugal clutches
- Four-stroke scooter engines

PERFORMANCE

API SL/CF

TYPICAL TEST DATA

Characteristic	Test Methods	SAE 15W-40	SAE 20W-50
Density at 15°C, kg/l	ASTM D4052	0.88	0.89
Kinematic viscosity at 100 °C,	ASTM D445	15.1	18.8
Cranking viscosity at -20°C,	ASTM D5293	6700	
Cranking viscosity at -15°C,	ASTM D5293		8400
Pour Point, °C	ASTM D97	-35	-30
Total Base Number, mg KOH/g	ASTM 2896	6.5	6.5
Sulphated Ash, %wt	ASTM D874	0.82	0.82
Elemental Analysis			
Zinc, %wt	X-Ray/ICP	0.111	0.111
Calcium, %wt	X-Ray/ICP	0.190	0.190
Phosphorus, %wt	X-Ray/ICP	0.101	0.101
Sulphur, %wt	X-Ray	0.241	0.241
Nitrogen, %wt	ASTM D5762	0.054	0.054



Health & Safety Note – Always maintain good levels of personal hygiene when handling engine oils. Wash hands and skin areas where contact has occurred and avoid ingestion. See applicable Material Safety data Sheet for further information.